-eyetech

EyeOn Elite Speech Generating Device

Product Specifications

SYSTEM FEATURES

Operating System	Windows 10 Pro (64-bit)
Processor	Intel Core i5-7Y54
Memory	8GB RAM
Storage	256GB SSD
Display	14" IPS LCD
	1080×1920 IPS
	10-Point Touchscreen
	Anti-Reflective Film
Camera	2MP Front Camera
	5MP Rear Camera
Eye Gaze	8MP Eye Gaze Camera
	21 in (55cm) Optimal Distance
Integrated Communications	Wireless LAN 802.11ac
	Bluetooth 4.0
	Infrared Environmental Controls
Ports	DC Power
	HDMI output
	3.5mm audio jack
	2 × USB 2.0
	2 x USB 3.0
	2 x 3.5mm Switch Ports
Buttons	Power On/Off
	Volume Up/Down
	Eye Gaze Reset
Battery Run Time	Up to 10 Hour Battery Life (at
& Power	80% brightness with
	PowerGrip)
	Input Voltage: 110/240V,
	Max1.7A
Dimensions & Weight	14.5 in (36.8 cm) x 10.0 (25.4
	cm) in x 2.7 in (6.8 cm)
	$(W \times H \times D)$
	7.8 lbs (3.5kg)
Mounting	Compatible with Rehadapt,
	Daessy & CJT mounting
	systems.
Audio	4 x Speakers
	1 x Microphone
Status Indicators	Power/Battery Status



SOFTWARE

SOFTWARE	
Included	OnBright Speech Generating
	Software, including:
	BrightSymbol
	BrightTalk
	BrightConnect
	BrightControl
ENVIRONMENTAL	32°F (0°C) to 104°F (40°C)
	Operational Temperature
	-4°F (-20°C) to 140°F (60°C)
	Storage Temperature
	10% to 90% Humidity Range
WARRANTY	2 Year Return-to-Depot
	Extended warranty programs
	available.
ACCESSORIES	
Included	PowerGrip, BumpGuard,
	Kickstand
COMPLIANCE	
United States	FDA Registered
	PDAC Coded
International	CE Marked
	MDR Compliant
TESTING & STANDARDS	
FCC	FCC SDOC (EMC): FCC 47 Part
	15 Subpart B, Part 15 C, and
	Part 15E
ΙΑΤΑ	
	UN 38.3 Safety Transportation
IEC	
	IEC 62368-1
	CE RED RF 2014/53/EU
CE	ROHS 2011/65/EU. EU
	2015/863
FTO	2013/003
ETSI	EN 301 489-1, -3, -17, -19
	EN 300 328
	EN 300 328 EN 301 893
	EN 301 893 EN 300 440
	EN 303 410