

## EyeOn Go Speech Generating Device

### Product Specifications



#### SYSTEM FEATURES

Operating System	Android 11
Processor	ARM-based MTK-8788
Memory	8GB RAM
Storage	128GB Flash Memory
Display	10" IPS LED 1920x1200 IPS 10-Point Touchscreen Anti-Reflective Film
Camera	2MP Front Camera 5MP Rear Camera
Integrated Communications	Wireless LAN: 802.11ac Bluetooth 4.1 Infrared Environmental Controls
Ports	DC Power Micro SD Micro HDMI Type D 3.5mm audio jack 2 x USB Type A 2 x 3.5mm Switch Ports USB-C Adapter
Buttons	Power On/Off Volume Up/Down 3 Hot Key Buttons to: Launch Speech Software Go to Android Home Screen Mute-Unmute Toggle
Battery Run Time & Power	Up to 38 Hour Battery Life (at 80% brightness with Accessory Pack) Up to 14 Hour Battery Life (at 80% brightness without Accessory Pack) Input Voltage: 110/240V, Max 1.7A
Dimensions & Weight	10.2 in (25.8cm) x 7.3 in (18.5cm) x 2.4 in (6.2 cm) (W x H x D) 3.4 lbs (1.53kg)
Mounting	Compatible with Rehadapt & Daessy mounting systems. Integrated mounting point for head trackers included.
Audio	4 x Speakers 2 x Microphone
Status Indicators	Power/Battery Status

#### SOFTWARE

Included	Speech Generating Software
Languages	English (US/UK/AU) French Swedish Hungarian Sinhalese Regional Indian languages Coming Soon: Italian & German

#### ENVIRONMENTAL

	32°F (0°C) to 104°F (40°C) Operational Temperature -4°F (-20°C) to 140°F (60°C) Storage Temperature 10% to 90% Humidity Range
--	---

#### WARRANTY

	2 Year Return-to-Depot Extended warranty programs available.
--	---

#### ACCESSORIES

Included	Go Strap, Go Case, Power Grip Accessory Pack, BumpGuard Case, Kickstand
Optional	USB-C Adapter, KeyGuards

#### COMPLIANCE

United States	FDA Registered PDAC Coded
International	CE Marked MDR Compliant

#### TESTING & STANDARDS

FCC	FCC SDOC (EMC): FCC 47 Part 15 Subpart B, (RF) Part 15C, (RF) Part 15E
IATA	UN 38.3 Safety Transportation
IEC	IEC 6060-1-2 Medical Device Safety
CE	CE RED RF 2014/53/EU ROHS 2011/65/EU, EU 2015/863 REACH 1907/2006